

SECTION 1: IDENTIFICATION

1.1. Product Identifier

Product Form: Mixture

Product Name: Excel Calcium Pellet

1.2. Intended Use of the Product

Melting Ice

1.3. Name, Address, and Telephone of the Responsible Party

Company

Scotwood Industries, Inc.
12980 Metcalf Ave. STE 240
Overland Park, Kansas 66213

Office: (913) 851-3500

Toll Free: (800) 844-2022

Fax: (913) 851-3377

1.4. Emergency Telephone Number

Emergency Number : (800)-844-2022 (Monday – Friday 8:00am-5:00pm CST)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

Classification (GHS-US)

Acute Tox. 4 (Oral) H302

Eye Irrit. 2A H319

2.2. Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US) :



GHS07

Signal Word (GHS-US) :

Warning

Hazard Statements (GHS-US) :

H302 - Harmful if swallowed.

H319 - Causes serious eye irritation.

Precautionary Statements (GHS-US) :

P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P280 - Wear protective gloves, protective clothing, eye protection, face protection, respiratory protection.

P301+P312 - If swallowed: Call a poison center/doctor if you feel unwell.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P330 - Rinse mouth.

P337+P313 - If eye irritation persists: Get medical advice/attention.

P501 - Dispose of contents/container according to local, regional, national, territorial, provincial, and international regulations.

2.3. Other Hazards

Other Hazards: Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions. When heated to decomposition, emits irritating fumes. May be corrosive to metals upon prolonged contact.

2.4. Unknown Acute Toxicity (GHS-US)

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

Excel Calcium Pellet

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	Classification (GHS-US)
Calcium chloride	(CAS No) 10043-52-4	Proprietary	Acute Tox. 4 (Oral), H302 Eye Irrit. 2A, H319
Sodium chloride	(CAS No) 7647-14-5	Proprietary	Not classified
Magnesium chloride	(CAS No) 7786-30-3	Proprietary	Not classified

The specific chemical identity and/or exact percentage of composition has been withheld as a trade secret.

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of First Aid Measures

First-aid Measures General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid Measures After Inhalation: When symptoms occur: go into open air and ventilate suspected area. Remove to fresh air and keep at rest in a position comfortable for breathing. Obtain medical attention if breathing difficulty persists.

First-aid Measures After Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Obtain medical attention if irritation persists. Wash contaminated clothing before reuse.

First-aid Measures After Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if irritation develops or persists.

First-aid Measures After Ingestion: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/Injuries: Causes eye irritation. Dust may cause mechanical irritation to eyes, nose, throat, and lungs.

Symptoms/Injuries After Inhalation: Inhalation of large amounts may cause respiratory irritation.

Symptoms/Injuries After Skin Contact: Skin contact with large amounts of dust may cause mechanical irritation.

Symptoms/Injuries After Eye Contact: Causes eye irritation.

Symptoms/Injuries After Ingestion: Harmful if swallowed. Ingestion is likely to be harmful or have adverse effects.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not considered flammable but may burn at high temperatures.

Explosion Hazard: Product is not explosive.

Reactivity: When heated to decomposition, emits irritating fumes. Corrosive to metals upon prolonged contact.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Other information: Do not allow run-off from fire fighting to enter drains or water courses.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Avoid breathing (dust, fumes). Avoid all contact with skin, eyes, or clothing.

6.1.1. For Non-emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

6.1.2. For Emergency Responders

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Ventilate area.

6.2. Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

6.3. Methods and Material for Containment and Cleaning Up

For Containment: Contain and collect as any solid.

Methods for Cleaning Up: Clear up spills immediately and dispose of waste safely. Recover the product by vacuuming, shoveling or sweeping. Contact competent authorities after a spill.

Excel Calcium Pellet

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.4. Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Additional Hazards When Processed: When heated to decomposition, emits irritating fumes. Contact with water causes an exothermic heat reaction, which may cause significant temperature rise. May be corrosive to metals upon prolonged contact.

Precautions for Safe Handling: Do not breathe dust, fumes.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Do not eat, drink or smoke when using this product. Wash hands and forearms thoroughly after handling.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep/Store away from extremely high or low temperatures, direct sunlight, heat, ignition sources, incompatible materials.

Incompatible Products: Strong acids. Strong bases. Strong oxidizers. Reactive metals.

Special Rules on Packaging: Keep only in original container.

7.3. Specific End Use(s)

Melting Ice

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

No Occupational Exposure Limits (OELs) have been established for this product or its chemical components.

8.2. Exposure Controls

Appropriate Engineering Controls

: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure all national/local regulations are observed. Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

: Protective goggles. Protective clothing. Gloves.



Materials for Protective Clothing

: Chemically resistant materials and fabrics. Corrosionproof clothing.

Hand Protection

: Wear chemically resistant protective gloves.

Eye Protection

: Chemical goggles or face shield.

Skin and Body Protection

: Wear suitable protective clothing.

Respiratory Protection

: Not required under normal conditions of use.

Other Information

: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State	: Solid
Appearance	: Pellets, white solid.
Odor	: Odorless.
Odor Threshold	: No data available
pH	: No data available
Evaporation rate	: No data available
Melting Point	: 772 °C (1422°F)
Freezing Point	: No data available
Boiling Point	: 160 °F (71.11 °C)
Flash Point	: No data available
Auto-ignition Temperature	: No data available
Decomposition Temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor Pressure	: No data available
Relative Vapor Density at 20 °C	: No data available

Excel Calcium Pellet

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Relative Density	: No data available
Specific Gravity	: 2.2
Solubility	: Soluble in water.
Partition coefficient: n-octanol/water	: No data available
Viscosity	: No data available

9.2. Other Information No additional information available

SECTION 10: STABILITY AND REACTIVITY

- 10.1 Reactivity:** When heated to decomposition, emits irritating fumes. Corrosive to metals upon prolonged contact.
- 10.2 Chemical Stability:** Stable under normal conditions.
- 10.3 Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.
- 10.4 Conditions to Avoid:** Direct sunlight. Extremely high or low temperatures. Incompatible materials. Contact with water causes an exothermic heat reaction, which may cause significant temperature rise.
- 10.5 Incompatible Materials:** Strong acids. Strong bases. Strong oxidizers. Reactive metals.
- 10.6 Hazardous Decomposition Products:** Hydrogen chloride. Chlorine. Sodium oxides. Oxides of magnesium.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information On Toxicological Effects

Acute Toxicity: Harmful if swallowed.

Excel Calcium Pellet	
ATE (Oral)	1063.83 mg/kg body weight
Calcium chloride (10043-52-4)	
LD50 Oral Rat	1000 mg/kg
LD50 Dermal Rat	2630 mg/kg
Sodium chloride (7647-14-5)	
LD50 Oral Rat	3 g/kg
LC50 Inhalation Rat	> 42 g/m ³ (Exposure time: 1 h)
Magnesium chloride (7786-30-3)	
LD50 Oral Rat	2800 mg/kg
LD50 Dermal Rat	> 2000 mg/kg

Skin Corrosion/Irritation: Not classified

Serious Eye Damage/Irritation: Causes serious eye irritation.

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Carcinogenicity: Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: Inhalation of large amounts may cause respiratory irritation.

Symptoms/Injuries After Skin Contact: Skin contact with large amounts of dust may cause mechanical irritation.

Symptoms/Injuries After Eye Contact: Causes eye irritation.

Symptoms/Injuries After Ingestion: Harmful if swallowed. Ingestion is likely to be harmful or have adverse effects.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Calcium chloride (10043-52-4)	
LC50 Fish 1	10650 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
EC50 Daphnia 1	2400 mg/l (Exposure time: 48 h - Species: Daphnia magna)
Sodium chloride (7647-14-5)	
LC50 Fish 1	5560 (5560 - 6080) mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [flow-through])
EC50 Daphnia 1	1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC 50 Fish 2	12946 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
EC50 Daphnia 2	340.7 (340.7 - 469.2) mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])

Excel Calcium Pellet

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Magnesium chloride (7786-30-3)	
LC50 Fish 1	1970 - 3880 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	140 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])

12.2. Persistence and Degradability No additional information available

12.3. Bioaccumulative Potential

Excel Calcium Pellet	
Bioaccumulative Potential	Not established.
Calcium chloride (10043-52-4)	
BCF fish 1	(no bioaccumulation)
Sodium chloride (7647-14-5)	
BCF fish 1	(no bioaccumulation)

12.4. Mobility in Soil No additional information available

12.5. Other Adverse Effects

Other Information : Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, and international regulations.

SECTION 14: TRANSPORT INFORMATION

14.1 In Accordance with DOT Not regulated for transport

14.2 In Accordance with IMDG Not regulated for transport

14.3 In Accordance with IATA Not regulated for transport

SECTION 15: REGULATORY INFORMATION

15.1 US Federal Regulations

Excel Calcium Pellet	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard
Calcium chloride (10043-52-4)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Sodium chloride (7647-14-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Magnesium chloride (7786-30-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

15.2 US State Regulations

Calcium chloride (10043-52-4)	
U.S. - Texas - Effects Screening Levels - Long Term	
U.S. - Texas - Effects Screening Levels - Short Term	
Sodium chloride (7647-14-5)	
U.S. - Texas - Effects Screening Levels - Long Term	
U.S. - Texas - Effects Screening Levels - Short Term	
Magnesium chloride (7786-30-3)	
U.S. - Texas - Effects Screening Levels - Long Term	
U.S. - Texas - Effects Screening Levels - Short Term	

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision date : 10/21/2014

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200. The specific chemical identity and/or exact percentage of composition has been withheld as a trade secret.

GHS Full Text Phrases:

Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A

Excel Calcium Pellet

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

H302	Harmful if swallowed
H319	Causes serious eye irritation

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

SDS US (GHS HazCom) - US